

WORKSAFE LED 2224 LED



Waterproof
3-Way Switch (On-Off-Flash)
Anti-Roll Tube
Deep Ribbed Case
Non-Slip Grip
Faceted Reflector
Lens Ring Accepts Wands
Crush-Resistant Case
Polycarbonate Lens



BUDGET APPROVED

Intrinsically Safe
Zone Zero Rating

Worldwide Safety
Standard:
IECEX
Exia IIC T4 iaD
T135C Ga
DA

European Safety
Standard:
ATEX II1GD
Exia IIC T4 iaDT135C

WORKSAFE LED 2217 LED




IMPACT
RESISTANCE



OUTPUT

BEAM
DISTANCE



RUN
TIME

WATERPROOF



PEAK BEAM
INTENSITY

UL Rating:
Class 1 Div 1
Groups A, B, C, D

T4 and Class I
Division 11


Groups E, F, G, T4

IMPACT
RESISTANCE



OUTPUT

BEAM
DISTANCE



RUN
TIME

WATERPROOF



PEAK BEAM
INTENSITY



2217LED Specifications

Unit Information

Model #: 2217LED / Item #15460
UPC-IC (12 Digit): 016731154608

Unit Dimensions

Length: 8.1 in. (20.6 cm)
Width: 2.3 in. (5.8 cm) at head

Master Pack Dimensions

Weight: 9.9 lbs. (4.5 kg)
Cube: 1.43 ft³ (0.04 m³)
Quantity: 24

Safety Approvals

UL Protection Methods
Intrinsically Safe
Divisions 1 & 2
Class I, II, III Div 1 Groups A-G
Class I, II, III Div 2 Groups A-G
Operating Temp T5

Specifications

Power Source: 2x 'D' Cell Alkaline
Light Source: LED
Life: 30,000 hrs
Runtime: 200 hrs
Light Output: 40 Lumens/ 1,946 Candelas
Beam Distance: 88 Meters
Weight (Without batteries): 5.0 oz (.13 kg)

Product Features

- For use in hazardous atmospheres
- Waterproof, IP67 rating
- 'Switch Guard' Prevents accidental lighting
- Three-way switch : On-Momentary-Off
- Anti-roll tube
- Faceted reflector for more light



WorkSafe™ Model # 2217LED

Accessories

<u>Accessories</u>	<u>Description</u>
23853	6 ½" Red Snap In Wand
23860	6 ½" Yellow Snap In Wand

