

WORKSAFE LED 2224 LED



- Waterproof
- 3-Way Switch (On-Off-Flash)
- Anti-Roll Tube
- Deep Ribbed Case
- Non-Slip Grip
- Faceted Reflector
- Lens Ring Accepts Wands
- Crush-Resistant Case
- Polycarbonate Lens



BUDGET APPROVED

Intrinsically Safe
Zone Zero Rating

Worldwide Safety
Standard:
IECEX
Exia IIC T4 iaD
T135C Ga
DA

European Safety
Standard:
ATEX II1GD
Exia IIC T4 iaDT135C

WORKSAFE LED 2217 LED




IMPACT
RESISTANCE



OUTPUT

BEAM
DISTANCE



RUN
TIME

WATERPROOF



PEAK BEAM
INTENSITY

UL Rating:
Class 1 Div 1
Groups A, B, C, D

T4 and Class I
Division 11

Groups E, F, G, T4

IMPACT
RESISTANCE



OUTPUT

BEAM
DISTANCE



RUN
TIME

WATERPROOF



PEAK BEAM
INTENSITY



2224LED Specifications

Unit Information

Model #: 2224LED / Item # 15720
UPC-IC (12Digit): 016731157203

Unit Dimensions

Length: 10.2 in. (25.1 cm)
Width: 2.3 in. (5.8 cm) at head

Master Pack Dimensions

Weight: 10.8 lbs. (4.9 kg)
Cube: 1.43 ft³ (0.04 m³)
Quantity: 24

Safety Approvals

UL Protection Methods
Intrinsically Safe
Divisions 1 & 2
Class I, II, III Div 1 Groups A-G
Class I, II, III Div 2 Groups A-G
Operating Temp T5

Specifications

Power Source: 3 x 'D' Cell Alkaline
Light Source: LED
Life: 30,000 hrs
Runtime: 250 hrs
Beam Distance: 88 meters
Light Output: 40 Lumens/ 1,930 Candelas
Weight (Without batteries): 6.0 oz (.17 kg)

Product Features

- For use in hazardous atmospheres
- Waterproof, IP 67 rating
- 'Switch Guard' prevents accidental lighting
- Anti-roll tube
- Faceted reflector for more light
- Three way switch: On-Momentary-Off



WorkSafe™ Model #2224LED

Accessories

23853
23860

Description

6 ½" Red Snap In Wand
6 ½" Yellow Snap In Wand

