

Ultra Compact Intrinsically Safe Radio with 5 Watt Power Output



IC-M85UL

5 W output power for hazardous locations approved by UL

* Land mobile channels for the USA version: 2 W

Intrinsically safe: Class I, Division 1, Groups C, D; Class II, Division 1, Groups E, F, G; Class III. T3C.

Non-incendive: Class I, Division 2, Groups A, B, C, D

ANSI/TIA-4950-B, ANSI/UL 121201

* When used with Icom BP-292UL battery pack

* Ambient temperature: -20°C to +60°C

Compact and lightweight commercial grade marine and land mobile hybrid radio

Covering 136–174 MHz land mobile frequency, in addition to VHF marine channels

700 mW powerful audio provides clear communications

Abundant Emergency Functions; Man Over Board, Man Down, and Lone Worker Alarms

Easy switch between channel groups (Marine ⇄ LMR) with a programmable multi-function button on the top panel

IP67 and MIL-STD-810G rugged construction

AquaQuake™ prevents audio degradation from a water-logged speaker

11 hours of long-lasting operating time (with BP-292UL, TX: RX: Standby = 5 : 5 : 90)

Optional speaker-microphone, HM-184UL

OPTIONS

BATTERY PACK  BP-292UL Rechargeable Li-ion battery 7.2 V/ 1910 mAh (min.) 2010 mAh (typ.).	DESKTOP CHARGER  BC-227^{*1} BC-123S^{*2} Charges the BP-292UL in 2.7 hours. (approx.)	CONNECTABLE TYPE CHARGER  BC-226^{*1} BC-228 Charges the BP-292UL in 2.7 hours. (approx.)  Connects up to six BC-226 units.
SPEAKER-MICROPHONE  HM-184UL Waterproof.	BELT CLIPS  MBB-3 MB-136 Alligator type. Swivel type.	BELT HANGERS  MB-96N MB-96F MB-96FL Swivel type. Fixed type. Long type.
CARRYING CASE  LC-191 Hard type. Charging is possible while the case is attached.	CIGARETTE LIGHTER CABLES & POWER SUPPLY CABLE  CP-23L CP-25H OPC-515L For use with the BC-227. For use with the BC-227. For use with the BC-227.	ANTENNA  FA-SC58V Same as supplied.

The IC-M85UL should only be used with the specified Intrinsically Safe approved options.
 DO NOT use the transceiver with any other equipment other than the above options.

Supplied accessories:

- BP-292UL, battery pack
- BC-227, desktop charger
- BC-123SA/SE*, AC adapter
- FA-SC58V, antenna
- MBB-3, Belt clip
- Hand strap

* May differ, depending on transceiver version.

SPECIFICATIONS

		IC-M85UL	
GENERAL		Marine channels	LMR channels
Frequency coverage	TX RX	156.025–157.425 MHz 156.050–163.275 MHz	136.000–174.000 MHz
Usable channel groups, Number of channels		INT, USA*, CAN, WX* channels (* Varies according to version)	100 LMR channels
Type of emissions (Channel spacing)	USA	16K0G3E (25 kHz)	11K0F3E (12.5 kHz)
	EXP	16K0G3E (25 kHz)	16K0F3E (25 kHz) 11K0F3E (12.5 kHz)
Power supply requirement		7.2 V DC nominal	
Current drain (approximate)	TX EXP	1.5 A (at 5 W)	0.9 A (at 2 W) 1.5 A (at 5 W)
	RX Max. audio		0.45 A 50 Ω
Antenna impedance		50 Ω	
Operating temperature range		–20 °C to +60 °C, –4 °F to +140 °F	–30 °C to +60 °C, –22 °F to +140 °F
Dimensions (W×H×D) (Projections not included)		56 × 92 × 34.1 mm, 2.2 × 3.6 × 1.3 in (With BP-292UL)	
Weight (approximate)		285 g, 10.1 oz (with BP-292UL, FA-SC58V and MBB-3)	
TRANSMITTER			
Output power (at 7.2 V DC)	USA EXP	5/3/1 W	2/1 W 5/3/1 W
Max. frequency deviation		±5.0 kHz	±5.0 kHz (Wide) ±2.5 kHz (Narrow)
Frequency stability		±5.0 ppm	
Spurious emissions		–70 dBc typical	
Hum and noise		40 dB	40 dB (Wide) 34 dB (Narrow)
Audio harmonic distortion		10% (at 60% deviation)	
Modulation limiting		60–100% of maximum deviation	
RECEIVER			
Sensitivity (at 12 dB SINAD)		0.25 μV typical	
Adjacent channel selectivity		70 dB typical	70 dB typical (Wide) 55 dB typical (Narrow)
Spurious response		70 dB typical	
Intermodulation		70 dB typical	
Hum and noise		40 dB	40 dB (Wide), 34 dB (Narrow)
Audio output power	Internal SP	700 mW typical (at 10% distortion with 12 Ω load)	
	External SP	700 mW (at 10% distortion with 8 Ω load)	

Measurements made in accordance with TIA/EIA-603.

All stated specifications are subject to change without notice or obligation.

Applicable U.S. Military Specifications & IP Rating

Standard	MIL 810 G	
	Method	Procedure
Low Pressure	500.5	I, II
High Temperature	501.5	I, II
Low Temperature	502.5	I, II
Temperature Shock	503.5	I–C
Solar Radiation	505.5	I
Rain Blowing/Drip	506.5	I, III
Humidity	507.5	II
Salt Fog	509.5	–
Dust Blowing	510.5	I
Immersion	512.5	I
Vibration	514.6	I
Shock	516.6	I, IV

Also meets equivalent MIL-STD-810-C, -D, -E and -F.

Ingress Protection Standard	
Dust & Water	IP67 (Dust-tight and waterproof protection)

Read all instructions enclosed with the transceiver carefully and completely before using the transceiver.

All stated specifications are subject to change without notice or obligation. Icom and the Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. AQUAQUAKE is a trademark of Icom Incorporated. All other trademarks are the properties of their respective holders.

Icom Inc. 1-1-32, Kamiminami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013

www.icomjapan.com

Icom America Inc.
www.icomamerica.com

Icom (Europe) GmbH
www.icomeurope.com

Icom (Australia) Pty. Ltd.
www.icom.net.au

Your local distributor/dealer:

Icom Canada
www.icomcanada.com

Icom Spain S.L.
www.icomspain.com

Icom Asia Co., Ltd.
www.icomasia.com

Icom Brazil
 E-mail: sales@icombrasil.com

Icom (UK) Ltd.
www.icomuk.co.uk

Icom France s.a.s.
www.icom-france.com